



| Part Number                           | Dia.<br>x<br>mm<br>(Inch)<br>(A) x (D) | Rubber ID<br>mm<br>(Inch)<br>(B) | bolt hole<br>mm<br>(Inch)<br>(a) | Base Plate<br>Hole<br>mm<br>(Inch)<br>(b) | Mounting<br>Plate<br>Thickness<br>mm<br>(Inch)<br>(T) | Collar<br>mm<br>(Inch)<br>(d) |
|---------------------------------------|--|----------------------------------|----------------------------------|---|---|-------------------------------|
|                                       |  |                                  |                                  |   |   |                               |
| TPI368w<br>TPI368<br>TPI368h          | 36 x 8<br>(1.42) x (.31)               | 16.6<br>(.65)                    | 16.6<br>(.65)                    | 20<br>(.79)                               | 6<br>(.24)  | 3<br>(.12)                    |
| TPI5620w<br>TPI5620<br>TPI5620h       | 56 x 20<br>(2.20) x (.79)              | 25<br>(.98)                      | 13<br>(.51)                      | 34.5<br>(1.36)                            | 15<br>(.59)   | 7.5<br>(.30)                  |
| TPI6720w<br>TP6720<br>TPI6720h        | 67 x 20.5<br>(2.64) x (.81)            | 28<br>(1.10)                     | 17.5<br>(.69)                    | 35.1<br>(1.38)                            | 16<br>(.63)   | 8<br>(.31)                    |
| TPI8220w<br>TPI8220<br>TPI8220h       | 82 x 20.6<br>(3.23) x (.81)            | 31<br>(1.22)                     | 20<br>(.79)                      | 50.8<br>(2)                               | 16<br>(.63)   | 8<br>(.31)                    |
| TPI822001w<br>TPI822001<br>TPI822001h | 80 x 20.6<br>(3.15) x (.81)            | 35<br>(1.38)                     | 20<br>(.79)                      | 46.7<br>(1.84)                            | 15<br>(.59)   | 7.5<br>(.30)                  |

| Quality<br><br>ShoreA<br>Duro | Axial Load/Deflection |                  |
|-------------------------------|-----------------------|------------------|
|                               | N at mm               | Lbs at Inch      |
| 43                            | 190 N at .8 mm        | 41 LBS at .03"   |
| 57                            | 500 N at .8 mm        | 105 LBS at .03"  |
| 68                            | 1200 N at .8 mm       | 260 LBS at .03"  |
| 43                            | 150 N at 1.8 mm       | 119 LBS at .07"  |
| 57                            | 1200 N at 1.8 mm      | 260 LBS at .07"  |
| 68                            | 2000 N at 1.8 mm      | 260 LBS at .07"  |
| 43                            | 800 N at 2.0 mm       | 173 LBS at .08"  |
| 57                            | 1600 N at 2.0 mm      | 346 LBS at .08"  |
| 68                            | 3400 N at 2.0 mm      | 735 LBS at .08"  |
| 43                            | 1800 N at 2.2 mm      | 390 LBS at .09"  |
| 57                            | 3400 N at 2.2 mm      | 735 LBS at .09"  |
| 68                            | 4600 N at 2.3 mm      | 1000 LBS at .09" |
| 43                            | 5000 N at 2.2 mm      | 1082 LBS at .09" |
| 57                            | 10000 N at 2.3 mm     | 2160 LBS at .09" |
| 68                            | 15000 N at 2.3 mm     | 3245 LBS at .09" |