



Part Number	Dia. x mm (Inch) (B) x (H)	bolt hole mm (Inch) (d)	Hole Seperation mm (Inch) (b)	Baseplate Thickness mm (Inch) (S)	Quality		Max. Static Com- pression Force (vertical)		Max. Static Shear Force (horizontal)	
					ShoreA Duro	Elastomer	kN	lbs	kN	lbs
TA1060w TA1060 TA1060	100 x 63.5 (3.94) x (2.5)	8 (.31)	76.2 (3)	3 (.12)	43 57 68	NR	1.4 3.2 5.2	315 720 1170	0.5 0.9 1.5	112 202 350
TA1582w TA1582 TA1582h	152 x 82 (5.98) x (3.23)	10.2 (.40)	125 (4.92)	4 (.16)	43 57 68	NR	3 5.5 8.9	680 1340 2000	0.9 1.6 2.7	200 360 600
TA1610w TA1610 TA1610h	160 x 100 (6.30) x (3.94)	12.7 (.5)	135 (5.31)	5 (.20)	43 57 68	NR	2.7 5 8.2	600 1130 1850	0.9 1.7 2.7	205 385 620
TA17575w TA17575 TA17575h	175 x 76 (6.89) x (2.99)	12.7 (.5)	146 (5.75)	5 (.20)	43 57 68	NR	6.5 12 19.5	1460 2700 4400	1.6 3.1 5	350 700 1120
TA1876w TA1876 TA1876h	180 x 76 (7.09) x (2.99)	12.7 (.5)	146 (5.75)	6 (.24)	43 57 68	NR	6.6 12.3 20	1500 2730 4500	1.5 3 4.9	340 680 1100
TA187601w TA187601 TA187601h	180 x 76 (7.09) x (2.99)	19.1 (.75)	146 (5.75)	6 (.24)	43 57 68	NR	6.6 12.3 20	1500 2730 4500	1.5 3 4.9	340 680 1100
TA1810w TA1810 TA1810h	180 x 100 (7.09) x (3.94)	12.7 (.5)	146 (5.75)	6 (.24)	43 57 68	NR	6.5 11.6 18.5	1460 2600 4160	1.7 3.2 5.3	380 720 1200
TA181001w TA181001 TA181001h	180 x 100 (7.09) x (3.94)	19.1 (.75)	146 (5.75)	6 (.24)	43 57 68	NR	6.5 11.6 18.5	1460 2600 4160	1.7 3.2 5.3	380 720 1200
TA2414w TA2414 TA2414h	240 x 140 (9.45) x (5.51)	19.3 (.76)	190 (7.48)	6 (.24)	43 57 68	NR	11 20 33	2470 4500 7420	3.2 6 9.7	720 1350 2180